

CSC 347 - Concepts of Programming Languages

Subtyping

Instructor: Stefan Mitsch



Learning Objectives

- ❓ What should the type relationship between parameterized types be?
 - Identify read and write restrictions on parametric types



Checked Casts

- Recall lecture on safety

```
1 class A { int x; }
2 class B extends A { float y; }
3 class C extends A { char c; }
4
5 void f (B b) {
6     A a = b;          // upcast always safe
7 }
8 void g (A a) {
9     B b = (B) a;      // downcast must be checked
10 }
11 f (new B()); // OK
12 g (new C()); // ClassCastException
```

? What makes upcasting safe? What makes downcasting unsafe?



Subtyping

- Static and dynamic type

```
1 A x = new A ();  
2 B y = new B ();  
3 x = y; // B ok when A expected
```

- Method parameters

```
1 void aConsumer (A x) { ... }  
2 aConsumer (new B()); // B ok when A expected
```

- Method results

```
1 B bProducer () { ... }  
2 A x = bProducer (); // B ok when A expected
```

- Safe to use an instance of `B` when an `A` is expected
- `B` is a *subtype* of `A` : written `B<:A`
 - If `y:B` and `B<:A` then `y:A` (upcast)
- Subtyping is not just subclassing: parametric polymorphism



Subtyping Order: Top

- Subtyping relation `<:` is a *partial order* on types
 - *reflexive*: `X<:X`
 - *transitive*: if `Duck<:Bird` and `Bird<:Animal` then `Duck<:Animal`
- Some PLs have a `Top` type: `X<:Top` for all `X` (greater than all other types)
- In Java: `java.lang.Object` above reference types
- In Scala: `scala.Any` above all types, `scala.AnyRef` above reference types

```
1 val xs:List[AnyRef] = List ("hello", List(1))
2 val ys:List[Any]    = List ("hello", 1)
```



Subtyping Order: Bottom

- Most PLs do not have a `Bottom<:X` for all `X` (less than all other types)
- In [Scala Type Hierarchy](#): `Nothing` is `Bottom` type
- ? What is `Bottom` useful for?
- Important for typing uses of `Nil`

```
1 val nil:List[String] = Nil
2 // Best type possible
3 val xs1:List[String] = "hello" :: nil
4 val xs2:List[Any]    = 1 :: nil
```

```
1 val nil:List[Nothing] = Nil
2 // Best type possible
3 val xs1:List[String] = "hello" :: nil
4 val xs2:List[Int]    = 1 :: nil
```

- `Nil : List[Nothing]` and `List[Nothing] <: List[X]`, so
`(X :: List[Nothing]) : List[X]`



Type-Invariant Containers

```
1 abstract class Animal { def name: String }
2 case class Bird(name: String) extends Animal
3 case class Cat(name: String) extends Animal
4
5 case class Box[X](var content: X)
```

- Create concrete boxes

```
1 val birdBox = Box(Bird("Feathers"))
2 val catBox  = Box(Cat("Fluffy"))
```

- Create an abstract box

```
1 var animalBox = Box[Animal](Bird("Feathers"))
2 animalBox.content = Cat("Fluffy")
```

- Alias boxes

```
1 animalBox = birdBox // does not compile
```

❓ Why not `animalBox = birdBox` ?

- Does not compile because `Box[Bird]` is not a subtype of `Box[Animal]`
- Box is **invariant** in its type parameter `X`



Type-Invariant Containers

? What would go wrong if we allow assignment?

```
1 val birdBox = Box(Bird("Feathers"))  
2 var animalBox: Box[Animal] = birdBox // does not compile
```

```
1 val animal = animalBox.content // ok, we can read bird as an animal
```

```
1 animalBox.content = Cat("Fluffy") // we can put a cat into an animal box
```

```
1 val bird: Bird = birdBox.content // but now the bird box contains a cat!
```

! Writing to aliased container would create type violations!



Type-Covariant Containers

? What if we disallow modifying boxes?

```
1 case class ImmutableBox[+X](val content: X)
```

- Create and alias boxes

```
1 val birdBox = ImmutableBox(Bird("Feathers"))
2 val animalBox: ImmutableBox[Animal] = birdBox // compiles
3 val animal = animalBox.content                // reading ok
4 animalBox.content = Cat("Fluffy") // immutable, cannot write
```

- `ImmutableBox` is **covariant** in `X`
- Covariance type annotation `+X` can only be applied to read-only structures



Scala Lists are Covariant

? What is the practical relevance?

```
1 def printAnimalNames(animals: List[Animal]) =  
2   for a <- animals do println(a.name)
```

- Print some concrete lists

```
1 val birds: List[Bird] = List(Bird("Feathers"), Bird("Chirpy"))  
2 val cats: List[Cat]   = List(Cat("Fluffy"), Cat("Whiskers"))  
3  
4 printAnimalNames(birds)  
5 printAnimalNames(cats)
```

- 💡 If `List` was not covariant, `printAnimalNames` with concrete arguments of type `List[Bird]` and `List[Cat]` would not compile!



Scala Arrays are Invariant

```
1 def printAnimalNames(animals: Array[Animal]) =  
2   for a <- animals do println(a.name)  
3  
4 val birds: Array[Bird] = Array (Bird("Feathers"), Bird("Chirpy"))  
5 printAnimalNames(birds)
```

- Compile error

```
1 printAnimalNames(birds)  
2           ^^^^^  
3           Found: (birds : Array[Bird])  
4           Required: Array[Animal]
```

- Scala arrays are invariant, but Java arrays are covariant



Covariant Wildcard

? How can we still print arrays generically?

- Use a covariant wildcard to make array read-only

```
1 def printAnimalNames(animals: Array[? <: Animal]) =  
2   for a <- animals do println(a.name)  
3  
4 val birds: Array[Bird] = Array (Bird("Feathers"), Bird("Chirpy"))  
5 printAnimalNames(birds) // compiles
```

- No way to write to `Array[? <: Animal]`

```
1 animals(0) = Cat("Fluffy")  
2           ^^^^^^^^^^^^^^^  
3           Found:    Cat  
4           Required: animals.T
```



What about Writing?

```
1 def putCat(box: Box[Cat]) =  
2   box.content = Cat("Fluffy")
```

- Unable to pass in a box of animal

```
1 val animalBox: Box[Animal] = Box(Cat("Whiskers"))  
2 putCat(animalBox)  
3     ^^^^^^^^^  
4     Found:    (animalBox : Box[Animal])  
5     Required: Box[Cat]
```

- Because the animal box could be a bird box

```
1 val animalBox: Box[Animal] = Box(Bird("Feathers"))  
2 putCat(animalBox)
```



Contravariance

? What if we disallow reading?

```
1 class MutableBox[-X](content: X):  
2   private var x: X = content  
3   def put(elem: X) : Unit = x = elem
```

- Create and alias boxes

```
1 def putCat(box: MutableBox[Cat]) = box.put(Cat("Fluffy"))  
2  
3 val animalBox: MutableBox[Animal] = new MutableBox(Cat("Whiskers"))
```

- `MutableBox` is **contravariant** in `X`
- Contravariance type annotation `-X` can only be applied to write-only structures



Contravariance allows Degraded Read

```
1 class MutableBox[-X](content: X):  
2   private var x: X = content  
3   def put(elem: X) : Unit = x = elem  
4   def get : Any = x  
5  
6 def putCat(box: MutableBox[Cat]) = box.put(Cat("Fluffy"))
```

- Create box and modify it

```
1 val animalBox: MutableBox[Animal] = new MutableBox(Bird("Feathers"))  
2 var animal: Any = animalBox.get  
3  
4 putCat(animalBox)  
5 animal = animalBox.get
```



Contravariant Wildcard

```
1 def addFluffy(cats: List[Cat]) =  
2   Cat("Fluffy") :: cats
```

- Add to a list of cats

```
1 val cats: List[Cat] = List(Cat("Whiskers"))  
2 val moreCats: List[Cat] = addFluffy(cats) // ok
```

- Add to a list of animals

```
1 val animals: List[Animal] = List(Bird("Feathers"), Cat("Whiskers"))  
2 addFluffy(animals)  
3           ^^^^^^^  
4           Found:    (animals : List[Animal])  
5           Required: List[Cat]
```



Contravariant Wildcard

```
1 def addFluffy(cats: List[? >: Cat]) =  
2   Cat("Fluffy") :: cats
```

- Contravariant wildcard `? >: X`
- Add to a list of animals

```
1 val animals: List[Animal] = List(Bird("Feathers"), Cat("Whiskers"))  
2 val more: List[Any] = addFluffy(animals)
```

- ? Can we do better than `List[Any]` ?



Contravariant Type Parameter

- Use a contravariant type parameter rather than a wildcard

```
1 def addFluffy[X >: Cat](cats: List[X]) =  
2   Cat("Fluffy") :: cats
```

- Add to a list of animals

```
1 val animals: List[Animal] = List(Bird("Feathers"), Cat("Whiskers"))  
2 val moreAnimals: List[Animal] = addFluffy(animals)
```



Variance Annotations Example

```
1 trait Source[+X] { def get () : X } // Covariant: read-only
2 trait Sink [-X] { def put (x:X) : Unit } // Contravariant: write-only
```

```
1 class Ref [ X] (var contents:X) // Invariant: read-write
2 extends Source[X] with Sink[X]:
3   def get () = contents
4   def put (x:X) = contents = x
```

- Create aliases

```
1 val ref: Ref[Bird] = Ref(Bird("Feathers"))
2 val src: Source[Animal] = ref
3 val snk: Sink[Duck] = ref
```

- Write to `snk`, read from `ref` and `src`

```
1 val d = Duck("Quack")
2 snk.put(d)
3 val r = ref.get()
4 val s = src.get()
```

- What are the static and dynamic types of `d`, `r`, and `s`?



Variance Annotations Example

```
1 trait Function[-X,+Y] { def apply(x:X) : Y } // Contravariant in X, covariant in Y
```

- Covariant use

```
1 // List[Int] <: Seq[Int], so Function[Int,List[Int]] <: Function[Int,Seq[Int]]
2 val increment: Function[Seq[Int],Seq[Int]] = new Function[Seq[Int],List[Int]]:
3   def apply(x: Seq[Int]) : List[Int] = x.map(_ + 1).toList
4 // Int <: Any, so Function[Seq[Int],Int] <: Function[Seq[Int],Any]
5 val length: Function[Seq[Int],Any] = new Function[Seq[Int],Int]:
6   def apply(x: Seq[Int]) : Int = x.length
```

- Contravariant use

```
1 def chain(f: Function[List[Int],Seq[Int]], g: Function[Seq[Int],Any]) =
2   (x:List[Int]) => g(f(x))
3 chain(increment, length)
```



Summary

- *Subtype polymorphism*: $B \leq A$ (B is a subtype of A)
- *Parametric polymorphism*: $T[X]$ parameterize class T with type parameter X
- Covariant, contravariant, and invariant parametric types for $B \leq A$

	Covariant	Contravariant	Invariant
Relationship	$T[B] \leq T[A]$	$T[A] \leq T[B]$	$T[A] \not\leq T[B]$
Collection	List[X]		Array[X]
Annotations	$T[+X]$	$T[-X]$	$T[X]$
Functions	$\text{Unit} \Rightarrow X$	$X \Rightarrow \text{Unit}$	$X \Rightarrow X$
	Readable	Writable	Read-write